

# Accessori / Accessories

MADE IN ITALY

			Cod.
	Modulo Bluetooth. Opzionale per: BIOS1 e BIOS2.	<i>Bluetooth module. Optional for: BIOS1 and BIOS2.</i>	12006730
	<b>Scheda R1:</b> Scheda espansione funzioni per la centralina di comando a contatti puliti. Opzionale per: ERMES2, CT3IND, CT INVERTER e BIOS2.	<b>Scheda R1:</b> Card providing extended functions for the control unit with dry contacts. Optional for: ERMES2, CT3IND, CT INVERTER and BIOS2.	12000760
	<b>Scheda R2:</b> Scheda espansione funzioni per la centralina di comando. Uscita contatto pulito per la gestione dell'elettroserratura e della luce di cortesia. Opzionale per: AV1, AS24 e BIOS2 ECO.	<b>R2 card:</b> Card providing extended functions for control unit. Connection for electrical lock and courtesy light. Optional for: AV1, AS24 and BIOS2 ECO.	12001703
	<b>RPEC1:</b> Regolatore di coppia a triac con uscita 230 Vac. Collegabile alla centralina tramite un comodo e pratico innesto guidato. Opzionale per: AV1.	<b>RPEC1:</b> Torque adjuster with triac, with 230 Vac output. Connectable to the control unit by a comfortable and practical coupling. Optional for: AV1.	12000445
	<b>REF16A:</b> Regolatore di coppia a triac a spunto fisso di 16A con uscita 230 Vac. Facilmente collegabile alla centralina grazie ad un pratico innesto guidato. Opzionale per: AV1.	<b>REF16A:</b> Torque adjuster with triac with 16A fixed starting, with 230 Vac output. Connectable to the control unit by a comfortable and practical coupling. Optional for: AV1.	12000455
	<b>24CBA:</b> Scheda carica batterie 24V ad innesto con controllo elettronico della carica. Opzionale per: ACTION, SCOR.AS e AS24.	<b>24CBA:</b> 24V battery charger card with electronic control of the charge level. Optional for: ACTION, SCOR.AS and AS24.	12000780
	Batterie ricaricabili di notevole capacità elettrica permette il funzionamento regolare dell'automazione in caso di black out. <b>Batteria 12V da 7.2 Ah.</b> Dim. (mm) W x D x H = 150 X 65 X 95 <b>Batteria 12V da 1.3 Ah.</b> Dim. (mm) W x D x H = 98 X 45 X 50	<i>Rechargeable battery with remarkable electrical power allows the regular operation of the automation during a black out.</i> <b>Battery 12V da 7.2 Ah.</b> Dim. (mm) W x D x H = 150 X 65 X 95 <b>Battery 12V da 1.3 Ah.</b> Dim. (mm) W x D x H = 98 X 45 X 50	61400056 61400053
	<b>Winter:</b> Scheda riscaldatore controllata in temperatura grazie ad una sonda di temperatura per motori 230 Vac. Regolazione tensione di riscaldamento attraverso comodi ponticelli.	<b>Winter:</b> Heater card for 230 Vac motors controlled through a thermostatic probe. Setting of heating voltage by means of comfortable jumper connections.	12000770
	Moduli radio in varie tecnologie adatti per ricevitori modulari e centraline con decodifica a bordo. Utilizzabile sia per Rolling code sia per Fix code.	<i>Radio modules of different technologies, suitable for modular receivers and control units with built-in decoding. Suitable for both Rolling code and Fixed code applications.</i>	
	<b>IB1.M</b> Modulo radio ibrido banda larga.	<b>IB1.M</b> Hybrid broad band radio module.	12005691
	<b>IB4TDA</b> Modulo radio ibrido banda stretta.	<b>IB4TDA</b> Hybrid narrow band radio module.	12005745
	V9083 Serratura elettrica, profilo cilindrico con contro bocchetta laterale, 12Vac 15VA.	V9083 Electrical lock, cylindrical profile, lateral plate, 12Vac 15VA.	64100185
	V06 Serratura elettrica, contro bocchetta verticale, 12Vac 15VA.	V06 electrical lock, vertical plate, 12Vac 15VA.	64100182
	Necessita di mezzocilindro.	Half-cylinder needed.	64100183
	KIT BATTERIE in box. 2 batterie 1.3Ah, cavo 1mt.	<b>BATTERIES KIT</b> in box. 2 batteries 1.3Ah, cable 1mt.	12000757